



# INSTALLATION INSTRUCTIONS

## Part Number 28-4210

This filter fits: See catalog for current applications

\* **FREE K&N® decal** To register your warranty, please see us online at [knfilters.com/register](http://knfilters.com/register). **FREE K&N® decal** \* Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last many seasons. Now you can protect the engine in your drag car from dust and debris on the track and in the pits with these filters. These units are engineered with two filter elements to provide maximum airflow and protection.

### INSTALLATION:

1. Install carbon bracket onto top of K&N air filter using the supplied ¼-20 bolt and nut. Note the position of the bracket in relation to the base of the filter in Fig 1.
2. Install filter from the underside of the scoop. It may be necessary to gently work the base of the filter into the groove of the scoop.
3. Mark the hole locations in the bracket and scoop for mounting, with locations marked drill holes using ¼" drill bit Fig. 2
4. Install hardware through scoop and bracket, keeping pressure on the filter into the groove of the scoop until all bolts are tightened.

**THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.**



Fig. 1



Fig. 2

### Cleaning Instructions:

#### 1. Apply Cleaner

Spray K&N Air Filter Cleaner onto both sides of the air filter until it completely saturates the pleated material.

A. Apply K&N Air Filter Cleaner to clean side of filter

B. Apply K&N Air Filter Cleaner to dirty side of filter

Allow cleaner to soak into both sides of air filter for 10 minutes to loosen the dirt. Do not let cleaner dry on air filter.

**CAUTION: THE USE OF ANY OTHER CLEANING SOLUTION OR METHOD COULD DAMAGE THE FILTER!**

#### 2. RINSE (SEE FIGURE 2)

Rinse off air filter with cool low-pressure water. Allow gravity to flush dirt out of air filter by applying water to the clean side of the filter; up and down the length of the pleats. Continue to rinse the filter until all traces of cleaner are gone. If the filter is extremely dirty it may be necessary to repeat steps 1 and 2. If there are spots of dirt remaining on the filter, spray each spot directly with cleaner, allow a few minutes for it to soak and repeat rinsing step.

#### 3. DRY

After rinsing, gently shake off excess water and allow filter to dry naturally.

**CAUTION: THE USE OF ANY OTHER DRYING METHODS (I.E. COMPRESSED AIR, DRYER HEATERS, HEAT GUNS) COULD DAMAGE FILTER.**

**US Patent Number; 7, 452, 395**